

SAFETY DATA SHEET

NuFlex® 480 Premium**SECTION 1: IDENTIFICATION****1.1. Product identifier**

Trade name: NuFlex® 480 Premium

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Adhesive
Restricted to professional and industrial use.

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **NUCO Inc.**
150 Curtis Dr.
Guelph
Ontario
N1K 1N5 Guelph
Canada
T: 1800 853 3984
www.sealantcentre.com

Contact person: Regulatory Team

E-mail: info@nucoinc.com

SDS date: 2026-02-03

SDS Version: 3.0

Date of previous version: 2026-01-19 (2.0)

1.4. Emergency telephone number

ChemTel Chemical Expert Assistance Hotline
T: +1-800-255-3924

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

Acute Tox. 4; H332, Harmful if inhaled.

Resp. Sens. 1; H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 STOT SE 3; H335, May cause respiratory irritation.
 Carc. 1B; H350, May cause cancer.
 STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Causes skin irritation. (H315)
 May cause an allergic skin reaction. (H317)
 Causes serious eye irritation. (H319)
 Harmful if inhaled. (H332)
 May cause allergy or asthma symptoms or breathing difficulties if inhaled. (H334)
 May cause respiratory irritation. (H335)
 May cause cancer. (H350)
 May cause damage to organs through prolonged or repeated exposure. (H373)

Precautionary statement(s):

General:

Not applicable.

▼ *Prevention:*

Obtain special instructions before use. (P201)
 Do not breathe vapour/mist. (P260)
 Wash hands thoroughly after handling. (P264)
 Use only outdoors or in a well-ventilated area. (P271)
 Contaminated work clothing should not be allowed out of the workplace. (P272)
 Wear eye protection/protective gloves. (P280)
 [In case of inadequate ventilation] wear respiratory protection. (P284)

▼ *Response:*

IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
 IF exposed or concerned: Get medical advice/attention. (P308+P313)
 Call a POISON CENTER/doctor if you feel unwell. (P312)
 Get medical advice/attention if you feel unwell. (P314)
 If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)
 If eye irritation persists: Get medical advice/attention. (P337+P313)
 If experiencing respiratory symptoms: Call a POISON CENTER/doctor (P342+P311)

	Take off contaminated clothing and wash it before reuse. (P362+P364)
▼ <i>Storage:</i>	Store in a well-ventilated place. Keep container tightly closed. (P403+P233)
<i>Disposal:</i>	Dispose of contents/container in accordance with local regulation. (P501)
<i>Hazardous substances:</i>	4,4'-methylenediphenyl diisocyanate Distillates (petroleum), hydrotreated middle 2,2'-methylenediphenyl diisocyanate;4,4'- methylenediphenyl diisocyanate;o-(p- isocyanatobenzyl)phenyl isocyanate;methylenediphenyl diisocyanate;diphenylmethane-4,4'- diisocyanate;diphenylmethane-2,4'- diisocyanate;diphenylmethane-2,2'-diisocyanate Isocyanic acid, polymethylenepolyphenylene ester 2,4-dioxo-1,3-diazetidene-1,3-diylbis[p- phenylenemethylene-p-phenylene] diisocyanate Isocyanic acid, polymethylenepolyphenylene ester, polymer with alpha-hydro-omega-hydroxypoly(oxy-1,2- ethanediyl)
<i>Additional labelling:</i>	Industrial use only.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Talc	CAS No.: 14807-96-6	10-30%		
4,4'-methylenediphenyl diisocyanate	CAS No.: 101-68-8	10-30%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 (SCL: 5.00 %) Carc. 2, H351 STOT RE 2, H373	
Distillates (petroleum), hydrotreated middle	CAS No.: 64742-46-7	5-10%	Carc. 1B, H350	[19]
2,2'-methylenediphenyl diisocyanate;4,4'-methylenediphenyl diisocyanate;o-(p-isocyanatobenzyl)phenyl	CAS No.: 26447-40-5	1-5%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 4, H332 Resp. Sens. 1, H334	

isocyanate;methylenediphenyl diisocyanate;diphenylmethane-4,4'-diisocyanate;diphenylmethane-2,4'-diisocyanate;diphenylmethane-2,2'-diisocyanate			STOT SE 3, H335 (SCL: 5.00 %) Carc. 2, H351 STOT RE 2, H373	
Isocyanic acid, polymethylenepolyphenylene ester	CAS No.: 9016-87-9	1-5%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373	
2,4-dioxo-1,3-diazetidino-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate	CAS No.: 17589-24-1	0.1-1%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373	
Isocyanic acid, polymethylenepolyphenylene ester, polymer with alpha-hydro-omega-hydroxypoly(oxy-1,2-ethanediyl)	CAS No.: 57636-09-6	0.1-1%	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an

	unconscious person water or other drink.
<i>Inhalation:</i>	Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.
<i>Skin contact:</i>	Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
<i>Eye contact:</i>	If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
<i>Ingestion:</i>	If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.
<i>Burns:</i>	Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. A sign warning of toxic materials shall be affixed the room and cupboard containing the product(s).

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

<i>Recommended storage material:</i>	Keep only in original packaging.
<i>Storage conditions:</i>	Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store protected against freezing.
<i>Incompatible materials:</i>	Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALBERTA

Talc

Long term exposure limit (8 hours) (mg/m³): 2

4,4'-methylenediphenyl diisocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Long term exposure limit (8 hours) (mg/m³): 0.05

Isocyanic acid, polymethylenepolyphenylene ester

Long term exposure limit (8 hours) (ppm): 0.005

Long term exposure limit (8 hours) (mg/m³): 0.07

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

Talc

Time-Weighted Average Limit (TWA): 2 mg/m³ (Talc - Containing no asbestos fibres, Respirable) ; 0.1 f/cc (Talc - Containing asbestos fibres)

Annotations:

E = The value is for particulate matter containing no asbestos and less than 1% crystalline silica.

K = Should not exceed 2 mg/m³ respirable particulate.

4,4'-methylenediphenyl diisocyanate

Time-Weighted Average Limit (TWA): 0.005 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): C 0.01 ppm

Annotations:

S(R) = The substance has the potential to produce sensitization by respiratory route.

OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

Talc

Time-Weighted Average Limit (TWA): 2 mg/m³ (R)(E) ; 2 f/cc (K)

Annotations:

(E) = The value is for particulate matter containing no asbestos and < 1 % crystalline silica.

(K) = Should not exceed 2 mg/m³ respirable particulate mass.

(R) = Respirable fraction.

4,4'-methylenediphenyl diisocyanate

Time-Weighted Average Limit (TWA): 0.005 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): C 0.02 ppm

Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario
Regulation 490/09 (Designated Substances)

QUEBEC

Talc

Long term exposure limit (8 hours) (mg/m³): 2

Annotations:

Rd = Respirable dust.

Note 1= The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%.

4,4'-methylenediphenyl diisocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Long term exposure limit (8 hours) (mg/m³): 0.051

Annotations:

EM = Exposure must be reduced to a minimum in accordance with section 42.

S = Sensitizer.

Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

Talc

Long term exposure limit (8 hours) (mg/m³): 2

4,4'-methylenediphenyl diisocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Short term exposure limit (15 minutes) (ppm): 0.015

The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	Do not recirculate outlet air that contain the substances. The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.
<i>Hygiene measures:</i>	Take off contaminated clothing and wash it before reuse.
<i>Measures to avoid environmental exposure:</i>	Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

<i>Generally:</i>	No specific requirements.
<i>Respiratory Equipment:</i>	No specific requirements.
<i>Skin protection:</i>	No specific requirements.
<i>Hand protection:</i>	No specific requirements.
<i>Eye protection:</i>	No specific requirements.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Paste
<i>Colour:</i>	Tan
<i>Odour:</i>	Mild
<i>Odour threshold (ppm):</i>	No data available
<i>pH:</i>	neutral to slightly alkaline
<i>Density (g/cm³):</i>	-
<i>Relative density:</i>	1.294 - 1.378
<i>Kinematic viscosity:</i>	No data available
<i>Particle characteristics:</i>	No data available

Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
<i>Softening point/range (°F):</i>	No data available.

<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	heavier than air
<i>Decomposition temperature (°C):</i>	No decomposition if stored and handled as prescribed/indicated

Data on fire and explosion hazards

<i>Flash point (°C):</i>	> 93.34
<i>Flammability (°C):</i>	Not classified as a flammability hazard
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	Not explosive

Solubility

<i>Solubility in water:</i>	Slightly soluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available
<i>Solubility in fat (g/L):</i>	No data available.

9.2. Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	VOC content = 45 g/L, 3.57% w/w (Contenu en COV)
<i>Oxidizing properties:</i>	Not classified as oxidizing

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Ignition source
Direct Sunlight
Frost

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

Talc has been classified by IARC as a group 3 carcinogen.

4,4'-methylenediphenyl diisocyanate has been classified by IARC as a group 3 carcinogen.

Isocyanic acid, polymethylenepolyphenylene ester has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data for the mixture, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data for the mixture, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data for the mixture, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

None of the components are listed

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
TDG	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to TDG, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Canadian lists

NDSL:

None of the components are listed

DSL:

Talc

4,4'-methylenediphenyl diisocyanate

Distillates (petroleum), hydrotreated middle

2,2'-methylenediphenyl diisocyanate;4,4'-

methylenediphenyl diisocyanate;o-(p-

isocyanatobenzyl)phenyl isocyanate;methylenediphenyl

diisocyanate;diphenylmethane-4,4'-

diisocyanate;diphenylmethane-2,4'-

diisocyanate;diphenylmethane-2,2'-diisocyanate

Isocyanic acid, polymethylenepolyphenylene ester

2,4-dioxo-1,3-diazetidine-1,3-diylbis[p-

phenylenemethylene-p-phenylene] diisocyanate

Isocyanic acid, polymethylenepolyphenylene ester,

polymer with alpha-hydro-omega-hydroxypoly(oxy-1,2-ethanediyl)

15.4. Restrictions for application

Industrial use only.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

Additional information

Not applicable.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335, May cause respiratory irritation.

H350, May cause cancer.

H351, Suspected of causing cancer.

H373, May cause damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ANSI = American National Standards Institute
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
DSL = Domestic Substances List
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HHNOC = Health Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NDSL = Non-domestic substances list
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PHNOC = Physical Hazards Not Otherwise Classified
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL = A specific concentration limit.
SOR = Statutory Orders and Regulations
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TDG = Transportation of Dangerous Goods
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
WHIMS = Workplace Hazardous Materials Information System

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022

The information contained in this Safety Data Sheet (SDS) to the best of our knowledge is believed to be accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made, and Nuco Inc. does not accept liability for any loss or damage that may occur from the use of this product. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to determine the suitability and completeness of such information and the product for such use. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

The safety data sheet is validated by

Regulatory Team

SDS date:

2026-02-03

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: CA-en